

LASER MEASURING TOOLS





Laser distance detector

HLDD07085

€39.00



Measuring Range:85m
Measuring Accuracy:±2.0mm
Laser Type:635nm, <1mW, Class 2
Function:single measurement/continuous measurement/indirect measurement/area measurement/Volume measurement/single pythagorean theorem measurement/double pythagorean plus/double pythagorean minus/double area measurement
Battery: 2*1.5 AAA
Operating temp:0°C ~ +50°C
Packed by double blister



Unit	Qty/Pack	Barcode
PCS		6942141821943

Self-leveling line laser

HLL156601

€ 84.00



Green laser level
Working range:0~35m
Levelling accuracy:±1.5mm@7m
Line accuracy:±1.5mm@7m
Levelling time:<3s
Self-levelling angle:<4°
Laser type:520±10nm
Laser Class II <1mW
With horizontal and vertical line function
Operating temperature:0~+40 °C
Storage temperature:-10~+50 °C
Batteries LR6 AA(1.5V)*3
Magnetic bracket*1
Packed by canvas bag



Unit	Qty/Pack	Barcode
PCS		6942141801853



Laser level and distance measuring kit

HLL260403 €90.00

Laser level and distance measuring kit
With 1pcs self-leveling line laser (HLL156601)
With 1pcs Laser distance detector (HLDD05086)
Self-leveling line laser (HLL156601)
Green laser level
Working range: 0~35m
Levelling accuracy: $\pm 1.5\text{mm}@7\text{m}$
Line accuracy: $\pm 1.5\text{mm}@7\text{m}$
Levelling time: < 3s
Self-levelling angle: < 4°
Laser type: 520±10nm
Laser Class II < 1mW
Laser distance detector (HLDD05086)
Measuring Range: 55m
Measuring Accuracy: $\pm 2.0\text{mm}$
Laser Type: 635nm, < 1mW, Class 2
Include:



Unit	Qty/Pack	Barcode
SET	4	8887915006967

Tripods for laser levels

HLLT01152 €40.00

5/8" & 1/4" Thread
1.2m Aluminum tripod
Suitable for
HLL156503, HLL156601, HLL306505, HL
L305205, HLL301200, HLL301201, UHLL
301201, HLL306502
Weight: 1.0 kg
Packed by label



Unit	Qty/Pack	Barcode
PCS		6925582140064

Tripods for laser levels

HLLT01573 €45.00

5/8" & 1/4" Thread
1.5m Aluminum tripod
Suitable for
HLL156503, HLL156601, HLL306505, HL
L305205, HLL301200, HLL301201, UHLL
301201, HLL301216, HLL3012165, UHLL
301216, HLL301205, HLL305206, HLL30
52063, UHLL3052063, HLL305308, HLL3
053085, UHLL3053085
Weight: 1.15 kg
Packed by color box



Unit	Qty/Pack	Barcode
PCS		8887915000774

Tripods for laser levels

HLLT01586 €50.00

1/4" Thread
1.5m Aluminum tripod
Suitable for
HLL156503, HLL156601, HLL306505, HL
L305205, HLL301200, HLL301201, UHLL
301201, HLL301216, HLL3012165, UHLL
301216, HLL301205
Weight: 1.3 kg
Packed by color box




Unit	Qty/Pack	Barcode
PCS		8887915006356

Digital multimeter

DM310002 €39.00

Display : TRUR RMS 6000 counts
DC/AC Current:
6000uA/60mA/600mA/10A
DC Voltage: 600mV/6V/60V/600V/1000V
AC Voltage: 600mV/6V/60V/600V/750V
Resistance: 600Ω/6kΩ/60kΩ/600kΩ/6M
Ω/60MΩ
Capaci-
tance: 10nF/100nF/1000nF/10uF/1000u
F/10mF/100mF
Frequen-
cy: 10Hz/100Hz/1000Hz/10kHz/100kHz/
1000kHz/10MHz
Duty cycle: 1%~95% $\pm(2.0\%+3)$
Non-contact voltage detection
live line or neutral Line distinguish
Diode test
Max/Min and Data hold
With backlight function




Unit	Qty/Pack	Barcode
PCS	10	6942141806995

Digital multimeter

DM410003 €60.00

Display : TRUR RMS 20000 counts
Auto Range
DC/AC
Cur-
rent: 200.00uA/2000.0uA/20.000mA/200
.00mA/10.000A
DC
Volt-
age: 200.00mV/2.0000V/20.000V/200.00
V/1000.0V
AC
Volt-
age: 200.00mV/2.0000V/20.000V/200.00
V/750.0V
Resistance: 200.00Ω/2.0000kΩ/20.000k
Ω/200.00kΩ/2.0000MΩ/20.000M
Ω/100.00 MΩ
Capaci-
tance: 20.00nF/200.0nF/2.000uF/20.00u



Unit	Qty/Pack	Barcode
PCS	6	6942141805837

Digital AC clamp meter

DCM62001 €25.00

Display : TRUR RMS 4000 counts
AC Current: 4A/40A/400A
DC/AC Voltage: 400mV/4V/40V/600V
Resistance: 400Ω/4kΩ/40kΩ/400kΩ/4M
Ω/40MΩ
Capaci-
tance: 4nF/40nF/400nF/4uF/40uF/400uF
/4mF
Data Hold
NCV
Diode test
Low battery indication
Auto power off
With 2pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141804632

DC/AC clamp meter

DCM62002 €49.00

Display : TRUR RMS 4000 counts
DC/AC Current: 4A/40A/400A
DC/AC Voltage: 400mV/4V/40V/600V
Resistance: 400Ω/4kΩ/40kΩ/400kΩ/4M
Ω/40MΩ
Capaci-
tance: 4nF/40nF/400nF/4uF/40uF/400uF
/4mF
Data Hold
Flashlight
NCV
Diode test
Low battery indication
Auto power off
With 2pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141808340

DC/AC clamp meter

DCM66002 € 60.00

Display : TRUR RMS 6000 counts
DC/AC Current:60A/600A
DC/AC Voltage:600mV/6V/60V/600V
Resistance:600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ
Capacitance:10nF/100nF/1000nF/10uF/1000uF/10mF/100mF
Frequency:10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz
Temperature:-40.0°C~1000.0°C(-40.0°F~1832.0°F)
NCV
Data Hold
Lowz
LPF(VFD)
Inrush current
Phase function



Unit	Qty/Pack	Barcode
PCS	5	6942141806391

DC/AC clamp meter

DCM610002 € 75.00

VA colour display screen
Display : TRUR RMS 6000 counts
DC/AC Current:60A/600A/1200A
DC Voltage:600mV/6V/60V/600V/1000V
AC Voltage:600mV/6V/60V/600V/750V
Resistance:600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ
Capacitance:60.00nF/600.0nF/6.000uF/60.00uF/600.0uF/6.000mF/60.00mF
Frequency:10Hz/100Hz/1000Hz/10kHz/100kHz/1000kHz/10MHz
Temperature:-40.0°C~1000.0°C(-40.0°F~1832.0°F)
Data Hold
Lowz
LPF(VFD)
Inrush current



Unit	Qty/Pack	Barcode
PCS	5	6942141808920

Electrical test kit

DM3069 € 35.00

3pcs/set, including as follow:
1pcs Digital AC clamp meter(D-CM62001)
1pcs Digital multimeter(DM360011)
1pcs AC voltage detector(VD100091)
Digital AC clamp meter
Display : TRUR RMS 4000 counts
AC Current:4A/40A/400A
DC/AC Voltage:400mV/4V/40V/600V
Resistance:400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ
Capacitance:4nF/40nF/400nF/4uF/40uF/400uF/4mF
Digital multimeter
Display : TRUR RMS 2000 counts
DC Voltage:200mV/2V/20V/200V/600V
AC Voltage:20V/200V/600V
DC Current:20mA/200mA/10A




Unit	Qty/Pack	Barcode
SET	10	6942141828980

Test pencil

HSDT33001 € 9.70

Test Voltage: AC 12-300V
LCD digital display
Sound and light alarm
Auto power off
Low-battery indication
With 1pcs LR03 AAA battery
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	20	6942141806902

Digital sound level meter

HETSL031 € 39.00

Measuring range:30-130dB
Dynamic range:50dB
Sound pressure accuracy:±1.5dB(94dB@1KHz), ±1.5dB(94dB@8KHz)
Frequency response:30Hz-8KHz
Microphone:Polarized capacitance microphone
With backlight function
With lower battery indication function
With 3pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141812125

Digital humidity&temperature meter

HETHT031 € 43.00

Ambient temperature:-20°C~60°C(-4°F~140°F)
Ambient humidity:0~100%
Web bulb temperature:-20°C~60°C(-4°F~140°F)
Dew point temperature:-20°C~60°C(-4°F~140°F)
With backlight function
With lower battery indication function
With 3pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141813511

Digital light luxmeter

HETLU031 € 42.00

Range:0~200000Lux(0~20000FC)
Resolution:1LUX/1FC
Accuracy:±(3%+5Lux) (at 2854°K incandescent lamps) ±(6%+5Lux) others
Cosine angle deviation characteristics:30°(±2%), 60°(±6%), 80°(±25%)
Spectral range: 320~730nm
With 3pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141816956

Wood moisture meter

HETWM031 € 38.00

Moisture measurement range: 2~70%
Moisture measurement accuracy: ±2%
Temperature range: 0~40°C
Temperature accuracy: ±1°C
Environment humidity: 20~90%RH
Environment temperature: 0~40°C
Response time: <1sec
With 3pcs LR03 AAA batteries
Packed by double blister



Unit	Qty/Pack	Barcode
PCS	10	6942141811739